



TECTUL

CHECK ANTIFRAUDE PVC

APLICACIONES



CARACTERÍSTICAS



MATERIALES



DATOS TÉCNICOS	
ATRIBUTO	DESCRIPCIÓN
Tipo de Válvula	Cheque antifraude PVC
Descripción	Válvula de retención con inserto metálico
Marca	PCP
Cuerpo	Cuerpo: PVC - Rosca: Bronce tipo DZR
Asiento	NBR
Extremos	Rosca NPT
Operación	Resorte
Clase PSIG	150 PSI a 23°C
Test	ANSI B1.20 - ASTM F1970.
Limites de temperatura	0°C a 60°C

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.

CARACTERÍSTICAS



Ideal para evitar la devolución de agua en la línea, mínimas pérdidas de presión (menor que 1 PSI)

MATERIALES



Cuerpo: PVC -
Rosca: Bronce tipo DZR

APLICACIONES



Idealmente en tanques aéreos o aplicaciones que lo requieran.

Última Revisión Marzo 2022



TECTUL

CHECK ANTIFRAUDE PVC

APPLICATIONS



CHARACTERISTICS



MATERIALS



TECNICAL DATA	
ATTRIBUTE	DESCRIPTION
Valve Type	PVC anti-fraud check
Description	Check valve with metal insert
Brand	PCP
Body	Body: PVC - Thread: Bronze type DZR
Seat	NBR
Extremes	NPT thread
Operation	Spring
PSIG class	150 PSI @ 23 ° C
Test	ANSI B1.20 - ASTM F1970.
Temperature limits	0 ° C to 60 ° C

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.

CHARACTERISTICS



Ideal to avoid refunds of water in the line, minimal losses pressure (less than 1 PSI)

MATERIALS



Body: PVC -
Thread: Bronze type DZRy

APPLICATIONS



Ideally in aerial tanks or applications that require it.