



TECTUL

Manguera Alimentos en Caucho

MATERIALES

APLICACIÓN

CARÁCTERÍSTICAS DIMENSIONALES



Datos técnicos

Nominal [in]	DI mm	DE mm	Refuerzos	W/P psi/BAR	B/P psi/BAR	Peso Aprox [Kg]
3/4	19	30,5	2	12/175	36/525	0,72
1	25,4	34	2	12/175	36/525	0,81
1-1/4	31,8	42	2	12/175	36/525	1,02
1-1/2	38,1	48	2	12/175	36/525	1,3
2	50,8	63	2	12/175	36/525	2,09
2-1/2	63,5	76	2	10/150	30/450	3,14
3	76,2	91	2	10/150	30/450	3,26
4	101,6	118	2	10/150	30/450	5,45
5	127	143	4	10/150	18/250	6

MATERIALES

Tubo interno de nitrilo blanco EPDM, refuerzo de poliéster con espiral de acero y cubierta de nitrilo.

APLICACIÓN

Utilizada para la succión y descarga de alimentos aceitosos y no aceitosos.

CARÁCTERÍSTICAS DIMENSIONALES

Varían de 3/4 a 5 pulgadas para adaptarse a diversas aplicaciones. Presentación por rollo de 60 metros.

Características adicionales

Presión máxima: 150 psi

Temperatura: -20°C a +100°C

Factor de seguridad: 1:3

Tubo interior en EPDM blanco para impedir que los contenidos no se contaminen.

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

Rubber Food Hose

APPLICATION

MATERIALS

DIMENSIONAL CHARACTERISTICS



Technical Data						
Nominal [in]	DI mm	DE mm	Reinforcements	W/P psi/BAR	B/P psi/BAR	Aprox Weight [Kg]
3/4	19	30,5	2	12/175	36/525	0,72
1	25,4	34	2	12/175	36/525	0,81
1-1/4	31,8	42	2	12/175	36/525	1,02
1-1/2	38,1	48	2	12/175	36/525	1,3
2	50,8	63	2	12/175	36/525	2,09
2-1/2	63,5	76	2	10/150	30/450	3,14
3	76,2	91	2	10/150	30/450	3,26
4	101,6	118	2	10/150	30/450	5,45
5	127	143	4	10/150	18/250	6

MATERIALS
White nitrile EPDM inner tube, polyester reinforcement with steel spiral and nitrile cover.

APPLICATION
Used for suction and discharge of oily and non-oily foods.

DIMENSIONAL CHARACTERISTICS
They range from 3/4 to 5 inches to accommodate various applications. Presentation per roll of 60 meters.

Additional characteristics
Maximum pressure: 150 psi
Temperature: -20°C to +100°C
Safety factor: 1:3
Inner tube in white EPDM to prevent the contents from being contaminated.

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.