



TECTUL

Manguera Multipropósito 200 psi



Datos técnicos					
Nominal [in]	DI mm	De mm	W/P psi/BAR	B/P psi/BAR	Peso Aprox [Kg]
3/16	5,0	11	200/13,8	600/41,4	0,14
1/4	6,0	13	200/13,8	600/41,4	0,15
5/16	8,0	16	200/13,8	600/41,4	0,2
3/8	10,0	17	200/13,8	600/41,4	0,22
1/2	13,0	20	200/13,8	600/41,4	0,3
5/8	15,8	25	200/13,8	600/41,4	0,45
3/4	19,0	28	200/13,8	600/41,4	0,5
1	25,4	35	200/13,8	600/41,4	0,7
1-1/4	31,7	44	200/13,8	600/41,4	1,2
1-1/2	38,0	53	200/13,8	600/41,4	1,5
2	50,8	66	200/13,8	600/41,4	1,9

MATERIALES
 Tubo interior de NBR.
 Refuerzo de poliéster de alta tensión.
 Cubierta de NBR.

APLICACIÓN
 Se usa en aplicaciones generales industriales, líneas de combustible en motores de vehículos.

CARÁCTERÍSTICAS DIMENSIONALES
 Medidas varían de 3/16" a 2".
 Presentación por rollos de 50 a 100 metros.

Características adicionales
 Temperatura: -40°C a +100°C.
 Factor de seguridad: 1:3.
 Resiste todo tipo de aceites, gasolinas y derivados del petróleo.

* Fotos y medidas referenciales, sujetas a cambios sin previo aviso por parte del proveedor o fabricante.



TECTUL

Multipurpose Hose 200 psi



Technical Data					
Nominal [in]	DI mm	DE mm	W/P psi/BAR	W/P psi/BAR	Aprox Weight [Kg]
3/16	5,0	11	200/13,8	600/41,4	0,14
1/4	6,0	13	200/13,8	600/41,4	0,15
5/16	8,0	16	200/13,8	600/41,4	0,2
3/8	10,0	17	200/13,8	600/41,4	0,22
1/2	13,0	20	200/13,8	600/41,4	0,3
5/8	15,8	25	200/13,8	600/41,4	0,45
3/4	19,0	28	200/13,8	600/41,4	0,5
1	25,4	35	200/13,8	600/41,4	0,7
1-1/4	31,7	44	200/13,8	600/41,4	1,2
1-1/2	38,0	53	200/13,8	600/41,4	1,5
2	50,8	66	200/13,8	600/41,4	1,9

MATERIALS
 NBR inner tube.
 High tension polyester reinforcement.
 NBR cover.

APPLICATION
 It is used in general industrial applications, fuel lines in vehicle engines.

DIMENSIONAL CHARACTERISTICS
 Measurements vary from 3/16" to 2".
 Presentation in rolls of 50 to 100 meters.

Additional characteristics

Temperature: -40°C to +100°C.
 Safety factor: 1:3.
 Resists all types of oils, gasoline and petroleum derivatives.

* Reference photos and measurements, subject to change without prior notice from the supplier or manufacturer.